

**Cvpcb.**

## **Rubriques**

[1 - Purpose](#)

[2 - 2 - General characteristics](#)

[2.1 - 2.1 - Characteristics](#)

[2.2 - 2.2 - Input netlist format](#)

[2.3 - 2.3 - Output Netlist](#)

[3 - 3 - Invoking Cvpcb](#)

[4 - CVPCB Commands](#)

[4.1 - Main screen](#)

[4.2 - Main Screen Toolbar](#)

[4.3 - CVPCB Configuration](#)

[4.3.1 - General screen](#)

[4.3.2 - Netlist Format](#)

[4.3.3 - Footprint Library selection](#)

[4.3.4 - Selecting the equivalence files](#)

[4.4 - Selecting library path and default extensions](#)

[4.5 - Viewing the current footprint](#)

[4.5.1 - Display](#)

[4.5.2 - Keyboard Commands](#)

[4.5.3 - Pop Up Menu](#)

[4.5.4 - 3D Display](#)

[5 - Associating components with footprints](#)

[5.1 - Principle](#)

[5.2 - Assignment](#)

[5.3 - Changing an existing assignment](#)

[6 - Equivalence files](#)

[6.1 - Purpose](#)

[6.2 - Format](#)

[7 - Back- annotation file](#)

### **1 - Purpose**

**CVPCB** allows you to assign each **component** that appears in the **netlist** created by the **Schematic** program to the name of the **footprint** which will represent it on a printed circuit board, and adds this information to the netlist.

Generally the **netlist** does not specify which **footprint** (i.e. the physical appearance of the component) the printed circuit software (**PCBNEW**) will have to display to create the general drawing of the card.

Components can be assigned to their corresponding footprints manually. You can create *Equivalence files*, which are look-up tables associating each component with its footprint. When equivalence files are available, automatic assignment is possible.

The list of the footprints available for the PCB software is contained in one or more **FOOTPRINT** libraries.

This interactive approach is much simpler than directly placing the assignments on the schematic, because as well as allowing automatic assignment, **CVPCB**, allows you to see the list of the footprints available, and to display them on the screen.

### **2 - 2 - General characteristics**

#### **2.1 - 2.1 - Characteristics**

## **Cvpcb.**

Interactive assignment of components with footprints or automatic assignment via equivalence files.

Generation (if necessary) of back- annotation files of this assignment to the schematic.

### **2.2 - 2.2 - Input netlist format**

- **EESchema** (without footprint references).
- **VIEW LOGIC WIRELIST**.
- **VIEW LOGIC NETLIST** \* (.NET+.PKG)

### **2.3 - 2.3 - Output Netlist**

Two files are generated for **Pcbnew**:

- The enhanced **Netlist** file (with footprint references)
- An auxiliary component assignment file . (**.CMP**).

## **3 - 3 - Invoking Cvpcb**

**cvpcb** (the file is then selected in **CVPCB**, via the file menu) or **cvpcb <filename>**, (**filename** being the name of the **netlist** file to be processed, from the schematic tool **Eeschema**).

The name of the file can be given with or without extension.

The extensions will if necessary be supplied by the defined in **cvpcb** configuration.

The two generated files will have the same name (with different extensions).

The standard extension of the file to be processed is **.net**.

The standard extension of the generated **netlist** file is **.net**, and will replace the old **.net**.


The standard extension of the file assigning components to the corresponding footprints (also generated by **CVPCB**) is **.cmp**.

These standard extensions can be modified by changing **Cvpcb** configuration.

## **4 - CVPCB Commands**

### **4.1 - Main screen**

## Cvpcb.



The **Component** window (on the left) displays the list of components appearing in the **Netlist** read.

The **footprint** window (on the right) displays the list of footprints contained in the libraries read.

The **component** window is empty if no file is loaded, and the **footprint** window can be also empty if no footprint libraries are found.

### 4.2 - Main Screen Toolbar



The various functions are:

	Select the <b>Netlist</b> file to be processed.
	Create the assignment (stuff) file <b>.CMP</b> and the <b>.NET</b> file, the modified, expanded <b>Netlist</b> .
	Invoke the <b>CVPCB</b> configuration menu.
	Display the current footprint (i.e. whose name is highlighted in the footprint window).
	Automatically assign components/footprints starting from the equivalence files. Using this order obviously assumes that these files are available.
	Automatically run through the components towards the beginning of the list


## Cvpcb.

	until the first component not yet assigned a footprint.
	Automatically run through the components towards the end of the list until the first component not yet assigned a footprint.
	Delete all assignments.
	Generate footprint assignment back-annotation file.
	Go to footprint documentation.

## 4.3 - CVPCB Configuration

### 4.3.1 - General screen

Invoking the configuration menu displays the following screen:



### 4.3.2 - Netlist Format

The options are:

#### **PcbNew:**

Read the netlist file generated by Eeschema, enhance it and generate the .cmp file.


#### **ViewLogic Wirelist:**

Accept standard format Viewlogic "Wirelist" (extension .wir) and generate a netlist file in PcbNew format (and the file .cmp)

#### **ViewLogicNet & Pkg:**

Accept the standard Viewlogic format netlist (.net) associated with the component file (.pkg) and generate a netlist file in Pcbnew format (and the .cmp file).

### 4.3.3 - Footprint **Library** selection




To select a file with the mouse:

- **Del** removes this name from the list.
- **Add** adds a new name to the list, **after the** selected name
- **Ins** adds a new name to the list, **before the** selected name.

**Note:**

Any modification of this list also affects **pcbnew**.

### 4.3.4 - Selecting the equivalence files



To select with the mouse a file name.

- **Del** removes this name of the list.
- **Add** adds a new name to the list, **after the** selected name
- **Ins** adds a new name to the list, **before the** selected name

## 4.4 - Selecting library path and default extensions



**Lib Dir** is the default path of the footprint file (**.mod**) and of the equivalence (**.equ**) files. If this field is left empty, the default path used will be **kicad/modules**.


Cvpcb.

## 4.5 - Viewing the current footprint

The **Visu** command allows display of the current footprint, i.e. the one that appears highlighted on the central line of the **footprint** window.

The various footprints can be displayed by clicking on the desired footprint (in the list of the footprints), as long as this window is in displayed.

One can also display the 3D view (if it has been created and assigned to the footprint)



### 4.5.1 - Display

The co-ordinates of the cursor are displayed at the bottom of the screen :


Absolute co-ordinates (X **nnnn** Y **nnnn**) and relative co-ordinates (**dx nnnn** **dy nnnn**)

The relative co-ordinates are zeroed by the space bar.

### 4.5.2 - Keyboard Commands

<b>F1</b>	Zoom In
<b>F2</b>	Zoom Out
<b>F3</b>	Refresh Display
<b>&lt;space bar&gt;</b> :	Zero relative co-ordinates.

### 4.5.3 - Pop Up Menu



Displayed by right-clicking the mouse:


<b>Zoom Selection (Select Zoom)</b>	Direct selection of the display zoom .
<b>Grid Selection (Grid Select)</b>	Direct selection of the grid.

### 4.5.4 - Toolbar



	Display Options
	Zoom Level
	3D Display

### 4.5.4 - 3D Display



## 5 - Associating components with footprints

Cvpcb.

## 5.1 - Principle

In the footprint window double-click on the name of the desired **footprint** (This name is **highlighted**), to assign it the **component** whose name is **highlighted on the central line** of the **component** window.

The next component in the list is selected:

- Automatically after an assignment.
- Manually using the mouse or cursor keys.

## 5.2 - Assignment

Double- click the **left mouse button** on the desired **footprint**

## 5.3 - Changing an existing assignment

This is done like a new assignment:

Double-click the **left mouse button** on the new desired **footprint**

## 6 - Equivalence files

### 6.1 - Purpose

These files allow automatic assignment.

They give the name of the corresponding footprint according to the name (value) of the component.

### 6.2 - Format

They consist of a line for each component.

Each line has the following structure:

**'component name' 'footprint name'**

Each name being framed by the letter ', the 2 names being separated by one or more spaces.

*Example:*

If the **U3** component is circuit 14011 and its footprint is 14DIP300, the line is:

"14011" "14DIP300"

## 7 - Back- annotation file

This a file can be used for back- annotation of a schematic but is not used by **PCBNEW**.

It consists of a line for each component, giving the name of the footprint according to its reference.

**Example:**

If the **U3** component was assigned the **footprint14DIP300**, the generated line is

**comp** "U3" = footprint "14DIP300"

The file created has the root name of the **CVPCB** input file, with extension **.stf**, and is placed in the same folder as the generated **netlist**.